Gas Station Light Series



200-1600w

Various Model Preference

165lm/wSupreme Lighting Efficiency

10KV Surge Protection **3000-6000K**CCT Choice







NF-HYG-FY1

NF-HYG-FY2













Energy conservation

Dustproof and Waterproof

Stable heat dissipation

Durable

High bright light source

Ultra low glare

Lighting Parameters

Models Types	NF-HYG-FY1-50	NF-HYG-FY1-100	NF-HYG-FY2-100
Luminaire Flux	7000lm	7000lm	14000lm
Input Voltage		A85-265 AC 50-60Hz	
LED Driver		Mean Well/ Inventronics	
Light Source	3030 88pcs	5050 16pcs	3030 152pcs
Light Efficiency		140-150 lm/w	
CRI		>80 Ra	
Beam Angel		15°/25°/36°/48°/60°/120°	
Product Dimension	234*234*60mm	234*234*60mm	324*324*65mm
Warranty Period		3-5 years	

Lighting Parameters

Models Types	NF-HYG-FY1-50	NF-HYG-FY1-100	NF-HYG-FY2-100
Luminaire Flux	14000-15000lm	21000-22000lm	28000-300000lm
Input Voltage		AC 100-277V	
LED Driver		Mean Well/ Inventronics	
Light Source		256 pcs/3030	
Light Efficiency		140-150 lm/w	
CRI		>80 Ra	
Beam Angel		30°/60°/90°/120°	
Product Dimension		340*340*96.5mm	
Warranty Period		3-5 years	











